



# Rhythm





# Rhythm

Fabric Rhythm is a true boucle beauty. It's smooth yarns, soft touch and excellent performance are the perfect ingredients for our Timeless Collection. The timeless collection represents all our creative essentials. Fabrics that offer the very best value for money and suit every style all year round.

Inspired by premium, heavy and luxury fabrics, we created upholstery fabric Rhythm. The look and feel of Rhythm will amaze and convince you.

The heavy weight of 950 grammes per meter suits the high-quality impression of the fabric. The twisted polyester yarns are smooth and soft to the touch. The fabric is yarn dyed and woven on a dobby loom. For easy processing we have applied a transparent coating.

All options for upholstery are suitable for this fabric. The tone-in-tone dyed yarns create a full and rich optic sense. The colours are chosen in subtle colour palette with a high-class vibe and machine-washable at 30 degrees Celsius\*.

Get in the flow of our Rhythm.

- Always be careful with sharp or rough objects such as watches, buckles or Velcro, as they may damage the fabric.
- When a loop does occur, it can be easily pushed back into the fabric with a blunt object.
- Please note that through daily use a certain hairiness may occur, this can easily be taken away with a pilling machine and has no further influence on the durability of this textile.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

**Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

## Composition

/ faceside 100%PES  
/ backside n/a  
/ flatweave

## Suitable for


sofa's, beds, chairs with fitted and loose fitting upholstery



anthracite 67



beige 05



blossom 166



blush 92



brick 128




brown 15



caramel 16




charcoal 79



clay 84



ecru 102



forest 162



grey 65


Please note: colours may vary according to your screen settings.



ivory 101



liver 10



natural 01



niagara 158



steel 149



thyme 206



wood 108

Please note: colours may vary according to your screen settings.



Rhythm - Article passport


A luxurious, smooth and soft boucle beauty.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	n/a	
Coating	transparent	
Statistic code	54075300	
Dyeing method	yarn dyed	
Available colours	19	
Packaging	transparent plastic	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 20.000	min. 40.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
gnitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 140							
Roll length in meters	± 25							
Material weight in grams per linear meter	± 950							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.830	803	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	300,3	371,1	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	3,8	1,6	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-1,0	-1,2	n/a	n/a	A/A



- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

